

PRODUCT DATA

PD 160

AQUARIGHT CTS 504

DESCRIPTION AND USE

AQUARIGHT CTS 504 is a blend of phosphonobutance compounds, selected homopolymer and dispersant, designed to control corrosion and prevent scale deposition in large re-circulating open cooling systems operating on serve make-up waters.

GENERAL SPECIFICATION

Appearance : Yellowish Specific Gravity : 1.07 pH : 12

TREATMENT AND DOSAGE REQUIREMENTS AQUARIGHT CTS 504 should normally be dosed continuously to maintain 100/C mg/l of product in the feed cooling system, although higher dosage may be recommended under abnormal or upset circumstances.

The correct treatment level will be recommended by your AQUARIGHT representative or agent to ensure reliable performence.

AQUARIGHT CTS 504 may be dosed direct to the system either neat or diluted as required in a mixing tank. Usage of a metering pump is strongly recommended.

PRODUCT BENEFITS

All organic, minimal envoirmental in pact.

Selected dispersant is a powerful threshold effect to control fouling over a wide range of conditions.

High concentrate product give a lower dosage rate and storage cost.

Resistant to degradation by oxidizing blocide regimes.

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.