



AQUARIGHT®
WE TREAT IT RIGHT

PRODUCT DATA

PD 112

AQUARIGHT T 012

DESCRIPTION AND USE

AQUARIGHT T 012 is liquid treatment based on a blend of tannins for use in hot water and steam raising boilers.

AQUARIGHT T 012 is provided to control corrosion and particulate solids in the system.

AQUARIGHT T 012 is a dual action product to be used in boilers with low hardness and de-aerated water.

GENERAL SPECIFICATION

Appearance : Brown
pH : 6 - 7
Specific gravity : 1.05

TREATMENT AND DOSAGE REQUIREMENTS

AQUARIGHT T 012 should be dosed continuously either direct to boiler or to the feed line / feed tank. The dosage rate will depend on the operating characteristics of the individual system and the water condition. The optimum treatment level will be specified by your AQUARIGHT representative or agent to ensure reliable performance.

PRODUCT BENEFITS

Dual action liquid product
Cost effective treatment
Easy to apply and test on site
Low toxicity product

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia