



AQUARIGHT®
WE TREAT IT RIGHT

PRODUCT DATA

PD 114

AQUARIGHT CTC 403

DESCRIPTION AND USE

AQUARIGHT CTC 403 is a synergistic formulation of zinc and organophosphonate.

AQUARIGHT CTC 403 combines very low corrosion rates and excellent scale prevention. It is used in large systems using medium hard waters, or hard waters plus acid dosing.

GENERAL SPECIFICATION

Appearance : Yellowish
Specific Gravity : 1.16
pH : 11.7

TREATMENT AND DOSAGE REQUIREMENTS

AQUARIGHT CTC 403 is normally maintained at concentrations between 50 and 70 mg/L in the circulating water. The correct treatment level depends on operating conditions such as pH, temperature and concentration factor of the water, and the mechanical design of the heat exchange plant.

AQUARIGHT CTC 403 should not normally be used above pH 8.5. The optimum treatment level, for any plant, will be specified by PT ZEFA VALINDO JAYA.

The viscosity of AQUARIGHT CTC 403 allows it to be handled by conventional dosage pumps, without dilution, but it may be diluted if desired.

AQUARIGHT CTC 403 is corrosive to mild steel. It may be pumped directly from the container using equipment in plastic.

PRODUCT BENEFITS

Cathodic inhibition.

Inhibits deposition.

May be dosed direct from drum.

Liquid product for ease of use.

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia