



AQUARIGHT®
WE TREAT IT RIGHT

PRODUCT DATA

PD 111

AQUARIGHT FR 001

DESCRIPTION AND USE

FR 001 is a blend of manganese and copper compounds. It also contains special emulsifying agents, to reduce fuel consumption, and prevent smut formation, soot deposits, corrosion and slag formation.

GENERAL SPECIFICATION

Appearance : Light brown
Specific gravity : 0.86
pH : 7 - 9

TREATMENT AND DOSAGE REQUIREMENTS

The preferred method of application is to add FR 001 to the storage tank/prior to bunkering, so that the associated turbulence cause mixing.

FR 001 is completely miscible and rapidly disperses in the tank.

The dose should be one part of FR 001 to 10.000 parts oil by weight, i.e. 1 liter FR 001 to 12 cubic meters oil;

PRODUCT BENEFITS

Reduces soot deposits and smut emission

Minimizes fireside corrosion

Reduces slagging

Softenes old fireside deposits

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia