



AQUARIGHT®
WE TREAT IT RIGHT

PRODUCT DATA

PD 106

AQUARIGHT MP 115

DESCRIPTION AND USE

AQUARIGHT MP 115 is a multipurpose boiler water treatment specifically designed for boilers that use hard make up water.

AQUARIGHT MP 115 contains a polymeric sludge conditioner, organic sequestrant, antifoam, phosphates and oxygen scavengers. This truly complete formulation offers outstanding performance benefits plus the convenience of a single liquid product.

GENERAL SPECIFICATION

Appearance : Brown
Specific Gravity : 1.32
pH : 10.5 (+/- 0.5)

TREATMENT AND DOSAGE REQUIREMENTS

Dosage depends upon the water quality and the operating characteristics of individual boiler system. Generally, dosage should be adjusted to provide a residual AQUARIGHT MP 115 in the boiler water, measured typically as 20 - 40 ppm as phosphate.

Continuous dosage in proportion to make up water is preferred. Dosage pumps of steel, cast iron, stainless steel and similar alloys may be used with this products. The optimum dosage will be specified by your AQUARIGHT representative or agent to ensure reliable performance.

PRODUCT BENEFITS

Can helps to minimize steam and condensate line corrosion

Easily to handle and on site test.

Complete product can be used in any type of boilers.

Every endeavor has been made to ensure that the information contained in this leaflet is reliable but we cannot accept liability for any loss, injury or damage which may result from its use. Data given in this Material Safety Data Sheet are solely for guidance in safe handling and use of the product(s) by customers; they do not form part of any specification. Customers are reminded that there may be uses or application of our products which are protected by patents under which PT ZEFA VALINDO JAYA have no rights. If any difficulties arise, we shall be glad to discuss them. Before using any product, read its label.

- a trade mark of : PT ZEFA VALINDO JAYA , Bekasi – Indonesia